

PB 55

Versions

SH (with gasoline engine)



Main features

- Direct throw sweeping system: longer brush life, longer filter life, longer run time, less dust created.
- Main brush and side brush adjustment.
- Lifting/lowering side brush lever on the control panel.
- Tough-robust and durable all steel plate body.
- Mechanical transmission on rear wheels.
- Battery-charge indicator (ET version).
- Cellulose dust panel filter and filter shaker.
- Horizontal filter for optimum dust control.
- Easy access for maintenance.
- Tilting rear handle bar.



Technical specifications	PB 55 ET	PB 55 SH
Cleaning path:		
- with main-brush only	50 cm	50 cm
- with main-brush + right side brush	68 cm	68 cm
Theoretical max. coverage rate per hour	2.700 mq	2.700 mq
Waste hopper capacity	36 l	36 l
Filtering surface (panel filter)	2 mq	2 mq
PROPELLING SYSTEM		
D.C. electric motor 12 V	600 W	-
Honda gasoline engine	-	3/4 kw/hp
Battery (voltage/capacity)	1x12/140 - 2x6/240 V/A-h	-
DIMENSIONS AND WEIGHT		
Length	134 cm	134 cm
Width	68 cm	68 cm
Height	98 cm	98 cm
Weight (empty) (*) without battery	92 kg	96 kg
ON REQUEST ACCESSORIES		
Electric filter shaker	SI	N.A.
No. 1 Battery 12V - 140 A/h	SI	N.A.
No. 1 Battery charger 1-phase 12V - 20 A/h	SI	N.A.
No. 2 Batteries 6V - 240 A/h	SI	N.A.
No. 1 Battery charger 1-phase 12V - 30 A/h	SI	N.A.

Technical specifications should be modified without notice